

Datum: 21.12.2024



Vklopni ventil »multifix« z nastavljivim gumbom, Velikost 5, G 1

Kategorija: [Start-up valves](#)
Šifra: **100629RIE**

(slika je simbolična)

Kratek opis

Start up valve »multifix«, with adjustable throttle, Size 5, G 1, Input pressure 2 - 16 bar, Medium / ambient temp. max. 60 °C

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems.

The full cross-section of the regulator is opened at 50% of the input pressure.

The filling time can be altered by turning the adjusting screw.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1 |
| Ohišje | Aluminium |
| Serijska | multifix |
| Tesnilo | NBR |
| Min. vhodni tlak [bar] | 2 |
| Velikost | 5 |
| Max. vhodni tlak [bar] | 16 |
| D [mm] | 52.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 99.7 |
| B [mm] | 104.0 |
| Pretok [l/min] | 16000 |