

**Datum:** 24.08.2024

## Vmesna plošča za ventilni terminal HDM, ločeni izpust

Kategorija: [Metalwork](#)Šifra: **106697RIE**

(slika je simbolična)

### Kratek opis

Intermediate plate for valve terminal HDM with separated exhaust (for multi-pressure systems, 2+4 are separately exhausted)

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates.

Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Monostable (non-latching) version of manual control also available on request.

The operating pressure is based on the installed input plates.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Ffunkcija	with separated exhaust (2+4 are separately exhausted)
IP zaščita	IP 65
Material	aluminium
Poskusno	Max. 16 (e.g. 16 spring return valves)
Ročno upravljanje	latching
Vhodna moč	0.6 W per pilot
Max. temperaturno območje [°C]	60