

Datum: 24.08.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Votli vijak, enotni, G 3/8

Kategorija: [Banjo bolt, single](#)  
Šifra: **108825RIE**

### Kratek opis

Hollow screw, Single, G 3/8, Working pressure -0.98 to 16 bar, Operating temperature -20 °C to 70 °C, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Nickel-plated brass
Navoj	G 3/8
Priporočena cev	PA, PU
Rokav	Hostaform
Serijska	click-clock
Vpenjalni obroč	Stainless steel
Max. delovni tlak [bar]	16
a/f [mm]	19
L1 [mm]	36.0
Max. delovna temperatura [°C]	70