

Datum: 03.11.2024



## Vrtljiva varnosta spojka I.D.11,serija za težko obrem. G3/8 N.N.

Kategorija: [Swivel safety couplings DN 11, heavy-duty series](#)  
Šifra: **141798RIE**

(slika je simbolična)

### Kratek opis

Swivel safety coupling I.D.11, heavy-duty series, Steel, G 3/8 IT, two-stage, Operating pressure max. 25 bar, Temp. -20°C to 100°C

High quality, robust and long lifetime rotation secure coupling, heavy duty design.

It is suitable for an extremely rough conditions.

To make a secure connection between the coupling and plug, the plug-in nipple is fed into the coupling and rotated to the right until the mechanism clicks in audibly. The connection is uncoupled in which the plug-in nipple is rotated to the left and at the same time the release ring is pulled backwards. The plug-in nipple is captured upon ejection from the safety chamber and only released after another left or right turn by 90°.

This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, manufacturing industry, offshore, refineries.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Delovni tlak	max. 25 bar / max. 16 bar when attaching / detaching at 6 bar and $\Delta_p = 0.5$ bar
Merjenje pretoka	bar
Navojni kos	Galvanised steel
Ohišje	Steel, QPQ treated
Povezava	G 3/8 IT
Rokav	Brass
Tesnilo	NBR
Ventil	Brass
Vzmet	Stainless steel
DN	11
a/f [mm]	36
Dolžina [mm]	75.0
Max. temperaturno območje [°C]	100
Pretok	2100 l/min (air)