

## Vtični T-kosa vrt., G 1/4 , zun. premera 6 mm



Kategorija: [Male branch tee, swivel type, parallel male thread](#)

Šifra: **135177RIE**

(slika je simbolična)

### Kratek opis

Push-in T-fitting, rotating, G 1/4 o., for hose exterior Ø 6 mm, Working pressure -0.98 - 20 bar, Stainless steel 1.4404  
For use in more aggressive environments and corrosive media.

The suitability test for the individual application is the user's responsibility.

### Tehnične Specifikacije

|                               |                           |
|-------------------------------|---------------------------|
| Min. delovna temperatura [°C] | -20                       |
| Min. temperatura medija [°C]  | -20                       |
| Min. delovni tlak [bar]       | -0.98                     |
| Material                      | Stainless steel<br>1.4404 |
| Navoj                         | G 1/4                     |
| Primerni materiali za cevi    | PVDF, PTFE, PA, PU        |
| Standardni navoj              | DIN EN ISO 228-1          |
| Tesnilo                       | FPM                       |
| Za cevi O.D. [mm]             | 6                         |
| a/f [mm]                      | 17                        |
| Max. delovni tlak [bar]       | 20                        |
| L2 [mm]                       | 28.0                      |
| L1 [mm]                       | 44.2                      |
| Max. delovna temperatura [°C] | 150                       |
| Max. temperatura medija [°C]  | 150                       |