

Vtični T-kosa vrt., G 3/8 , zun. premera 10 mm



Kategorija: [Male branch tee, swivel type, parallel male thread](#)

Šifra: **135182RIE**

(slika je simbolična)

Kratek opis

Push-in T-fitting, rotating, G 3/8 o., for hose exterior Ø 10 mm, Working pressure -0.98 - 20 bar, Stainless steel 1.4404
For use in more aggressive environments and corrosive media.

The suitability test for the individual application is the user's responsibility.

Tehnične Specifikacije

| | |
|-------------------------------|---------------------------|
| Min. delovna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Min. delovni tlak [bar] | -0.98 |
| Material | Stainless steel 1.4404 |
| Navoj | G 3/8 |
| Primerni materiali za cevi | PVDF, PTFE, PA, PU |
| Standardni navoj | DIN EN ISO 228-1 |
| Tesnilo | FPM |
| Za cevi O.D. [mm] | 10 |
| Max. delovni tlak [bar] | 20 |
| a/f [mm] | 21 |
| L2 [mm] | 30.7 |
| L1 [mm] | 48.6 |
| Max. delovna temperatura [°C] | 150 |
| Max. temperatura medija [°C] | 150 |