

Datum: 24.08.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Vtični T-kosa vrtljivi, R 1/2 o. Za cev zunanja Ø 10 mm

Kategorija: [Male branch tee, swivel type, conical male thread](#)
Šifra: **135201RIE**

Kratek opis

Push-in T-fitting, rotating, R 1/2 o., for hose exterior Ø 10 mm, Working pressure -0.98 - 20 bar, Stainless steel 1.4404
For use in more aggressive environments and corrosive media.

The suitability test for the individual application is the user's responsibility.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Stainless steel 1.4404
Navoj	R 1/2
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Standardni navoj	ISO 7-1
Za cevi O.D. [mm]	10
Max. delovni tlak [bar]	20
a/f [mm]	22
L2 [mm]	37.5
L1 [mm]	48.6
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150