

Datum: 24.08.2024

Vtični T-okovja univerz.kratkem L-oblike, ki se vrti 1/2, hose10

Kategorija: [Male branch tee, L-shape, swivel type, taper seat](#)
Šifra: **153325RIE**

(slika je simbolična)

Kratek opis

Male branch tee »universal short«, L-shape, rotating 1/2, hose-Ø10, taper seat, Working pressure -0,99 to 20 bar, nickel-plated brass

The quick-connect fittings of the »universal short« series are true to their name and are used for the quick and simple connection of hoses. The conical sealing threads offer a high degree of flexibility, as it is compatible with both conical and cylindrical threads. Thus the quick-connect fitting can be combined with a wide variety of thread types (BSPP, BSPT, NPT, NPTF, PT, PF) of standards ISO 7.1 and ISO 228. Shorter assembly times result from the reduced thread length. The smaller hole spacing, resulting from the reduction of the width across flats, enables installation in very tight spaces. This saves time and space.

The complete sealing is also guaranteed on uneven, for example inclined, concave or convex surfaces, and with differing radii and chamfers. The special geometry of the seal enables vacuum applications.

Areas of application: Pneumatic automation, automotive industry, textile and packaging industry, compressed air circuits, vacuum applications.

Tehnične Specifikacije

| | |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20 |
| Min. delovni tlak [bar] | -0.99 |
| Material | Nickel-plated brass |
| Priporočena cev | PA, PU, PTFE |
| Rokav | POM |
| Serija | universal short |
| Tesnilo | NBR |
| Vpenjalo | Stainless steel |
| Navoj | 01. Feb |
| Za cevi O.D. [mm] | 10 |
| Max. delovni tlak [bar] | 20 |
| a/f [mm] | 21 |
| L2 [mm] | 26.5 |
| L1 [mm] | 55.0 |
| Max. delovna temperatura [°C] | 80 |