

Datum: 22.07.2024



(slika je simbolična)

## Zaklep hid. spojke na obojstransko, Med.G 1/2 N.N.I.D. 11

Kategorija: [Hydraulic couplings, bright brass, female](#)  
Šifra: **107696RIE**

### Kratek opis

Hydraulic coupling locking on both sides, Bright brass, G 1/2 IT, I.D. 11, Operating pressure max. 150 bar, Temp. -20°C to 100°C

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Areas of application: machine and plant engineering, manufacturing industry, chemical / pharmaceutical industry, automotive, food technology.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	Referred to medium temp. of 50 °C, static working pressure
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta_p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	G 1/2 IT
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Tesnilo	NBR
Ventil	Brass with a bare metal surface
Vzmet	Stainless steel
DN	11
a/f [mm]	27
Dolžina [mm]	76.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Max. obratovalni tlak [bar]	150
Volumski pretok (zrak) [l/min]	1950