

Datum: 01.09.2024



(slika je simbolična)

Zaščitna spojka s tipko z N.N.I.D. 6, ISO 6150 C, G 1/2 N.N.

Kategorija: [Pushbutton safety coupling DN 6, female](#)
Šifra: **141929RIE**

Kratek opis

Pushbutton safety coupling I.D. 6, ISO 6150 C, Stainless steel, G 1/2 IT, Operating pressure max. 12 bar, Temp. -20 °C to 200 °C

"

High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand.

When pushed for the first time the coupling is vented, the plug remains securely in the coupling.

After a second push the plug is released.

This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded.

The safety version meets ISO standard DIN EN ISO 4414.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.

"

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Gumb	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 1$ bar
Navojni kos	Galvanised steel
Ohišje	Stainless steel
Povezava	G 1/2 IT
Tesnilo	FKM
Ventil	Brass
Vtični profil	acc. ISO 6150 C
Vzmet	Stainless steel
DN	6
Max. obratovalni tlak [bar]	12
a/f [mm]	24
Dolžina [mm]	58.0
Max. temperaturno območje [°C]	200
Pretok	1150 l/min (air)