



Združeni vakumsko/tlačno stikalo, polikarbonat

Kategorija: [Combined vacuum/pressure switch](#)
Šifra: **108421RIE**

(slika je simbolična)

Kratek opis

Combined vacuum / pressure switch, Polycarbonate, Measurement range -1-10 bar, Plug M8, 4-pole, G 1/8 ET, M5 IT, Temp. 0°C to 50°C
Universal electronic vacuum and pressure switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation directly at the point of use. Suitable for all special applications in the vacuum and compressed air sectors. Adjustable vacuum limit value and continuous vacuum monitoring.

Tehnične Specifikacije

Merilno območje min. bar	-1
Električni priključek	Male connector M8, four pin
G 1	G 1/8 ET
G 2	M5 IT
G 3	M8x1 ET
histereza	Adjustable: 3 to 25% of set value
izhodni signal	Analogue: 1 to 5 V
Izmerjena srednja povezava	G 1/8 ET and M5 IT
Navedba	LED
Ohišje	Polycarbonate
Srednje	Non-aggressive gases, dry, oil-free air
Vrsta gradnje	PNP
Merilno območje max. bar	10
Operativna napetost	10.8 to 30 V DC
Trenutna poraba [mA]	30
L [mm]	44.0
Max. temperaturno območje [°C]	50
L1 [mm]	62.0
Preklopna zmogljivost	125 mA